

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 February 2005 (10.02.2005)

PCT

(10) International Publication Number
WO 2005/012433 A1

(51) International Patent Classification⁷: **C08L 95/00**, C08K 5/17, 5/52

(74) Agent: ANDERSSON, Rolf; Akzo Nobel Surface Chemistry AB, S-444 85 Stenungsund (SE).

(21) International Application Number:
PCT/SE2004/001003

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 23 June 2004 (23.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0302161-5 1 August 2003 (01.08.2003) SE

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): AKZO NOBEL NV [NL/NL]; P.O. Box 9300, NL-6800 SB Arnhem (NL).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 2005/012433 A1

(54) Title: PROCESS FOR THE MANUFACTURE OF A BITUMEN-AGGREGATE MIX SUITABLE FOR ROAD PAVEMENT

(57) Abstract: The present invention relates to an aqueous quick-setting bitumen-aggregate mix suitable for cold pavement of roads, parking places, sidewalks and the like. The bitumen-aggregate mix is manufactured by mixing a mineral aggregate, water, a de-emulsifier, containing hydraulic cement, and a cationic oil-in-water bitumen emulsion, containing, as an emulsifier, a salt of a tertiary diamine and a phosphoric acid. The diamine has the formula (I), where one or two of the groups R₁, R₂, R₄ and R₅ designate a hydrocarbon group of 6-22, preferably 8-20 carbon atoms, and the remaining R₁, R₂, R₄ and R₅ groups are an alkyl group with 1-4 carbon atoms, and/or a group -(A)_nH, where A is an alkyleneoxy group with 2-3 carbon atoms, and s is a number from 1-4, R₃ is an alkylene group with 2-4 carbon atoms and n is a number from 0-2.